

INTERIOR WOOD PRODUCT SELECTION GUIDE



INTERIOR WOOD STAIN
Provides excellent penetration and grain enhancement that accentuates wood's natural beauty

- Clear Coat formula allows for a beautifully even color while retaining flexibility and top wear
- 25-30 minutes, recoat in 2 hours
- Ideal for all bare or newly finished wood surfaces such as cabinets, furniture, trim and doors



OIL BASED CLEAR GLOSS/SATIN FAST DRY VARNISH
Provides a smooth, fast-drying wood finish that adds to beauty.

- Offers a rich amber finish that provides good durability
- Two coat system that can be completed in 4 hours
- Use on interior wood surfaces such as trim and doors
- Excellent durability on surfaces exposed to hand wear or direct sunlight. Not recommended for use on floors or upholstery



CLEAR SANDING SEALER

Produces an extremely smooth, level finish on wood surfaces.

- This pre-treatment seals in an alternative to the first coat of the Quick-Dry Dry Varnish
- High film, UV rays to prevent graying and yellowing
- Fast drying, ready to sand in 1 hour
- Ideal for indoor stained surfaces such as trim, molding, cabinets, and furniture.



OIL BASED CLEAR GLOSS/SATIN POLYURETHANE

Provides a highly durable, tough, and flexible finish on high wear surfaces.

- Offers a clear finish that repels damage from chemicals, staining, water and common household chemicals
- Clear coat finish - 2-4 hours and can be recoated in 24 hours
- Ideal for all indoor wood surfaces such as trim, molding, cabinets, and woodwork



OIL BASED CLEAR GLOSS SPAR VARNISH

Provides a smooth and flexible finish that adds and helps protect wood surfaces exposed to rain, water, and temperature extremes.

- Offers a tough, flexible coating that repels damage from chemicals, stains, and adverse weather conditions
- High film, UV rays to prevent graying and yellowing extra protection against moisture
- Dries to touch in 3-4 hours, recoat in 24 hours
- Ideal for exterior and interior wood surfaces such as trim, molding, cabinets, and furniture



WATER BASED CLEAR GLOSS/SATIN POLYURETHANE

Provides a crystal clear wood finish that provides long-lasting protection.

- Offers a durable finish that resists damage from staining, mold, mildew, chemicals
- Dries quickly allowing multiple coats in 1 day
- Ideal for all indoor wood surfaces such as trim, molding, doors, trim, doors, and cabinets



INTERIOR WOOD STAIN COLORS

Walnut Oak	Walnut Red	Golden Oak	Golden Oak	Walnut Oak	Walnut Oak
Walnut Red	Walnut Red	Dark Walnut	Dark Walnut	Walnut Red	Walnut Red
Walnut Oak	Walnut Red	Golden Oak	Golden Oak	Walnut Oak	Walnut Oak
Walnut Red	Walnut Red	Dark Walnut	Dark Walnut	Walnut Red	Walnut Red
Walnut Oak	Walnut Red	Golden Oak	Golden Oak	Walnut Oak	Walnut Oak
Walnut Red	Walnut Red	Dark Walnut	Dark Walnut	Walnut Red	Walnut Red
Walnut Oak	Walnut Red	Golden Oak	Golden Oak	Walnut Oak	Walnut Oak
Walnut Red	Walnut Red	Dark Walnut	Dark Walnut	Walnut Red	Walnut Red
Walnut Oak	Walnut Red	Golden Oak	Golden Oak	Walnut Oak	Walnut Oak
Walnut Red	Walnut Red	Dark Walnut	Dark Walnut	Walnut Red	Walnut Red
Walnut Oak	Walnut Red	Golden Oak	Golden Oak	Walnut Oak	Walnut Oak
Walnut Red	Walnut Red	Dark Walnut	Dark Walnut	Walnut Red	Walnut Red

Wood stain colors represent a medium coat of stain applied to oak and pine that has been sanded after application. The color may vary on other woods and finishes. For more information on our products, visit our website at www.bestlook.com or call 1-800-284-1174. Questions about staining? Call toll free 1-800-284-1174.

BEST LOOK

INTERIOR WOOD STAIN PROGRAM



A COMPLETE INTERIOR WOOD PROGRAM DESIGNED TO HELP PROTECT AND REVITALIZE WOOD SURFACES
Best Look's Interior Wood Stain products enhance the appearance of your interior wood surfaces such as trim, molding, cabinets, doors, floors, and more while helping to prevent and reverse the wood's natural beauty against wear with maximum durability. Highlight and showcase your home's wood surfaces from start to finish with the Best Look's Interior Wood Stain, Sealers, Varnishes, and Polyurethanes.



The Best Quality Finishes

BEST LOOK

EXTERIOR WOOD STAINS

COLOR GALLERY

BEST LOOK EXTERIOR WOOD STAINS

BEST LOOK EXTERIOR LATEX SOLID COLOR DECK & SIDING

Provides a solid, opaque finish for exterior wood surfaces while offering the texture of the wood to the touch. This penetrating product provides maximum water repellency, durability and UV protection. It also provides a moisture and mold-repelling surface on bare or weathered wood and composite decking.

BEST LOOK EXTERIOR TRANSPARENT DECK & SIDING STAINS

Available in Clear and/or Tinted. These products provide excellent penetration and fast color change, allowing the grain and texture to show through. The stain and primer formulas penetrate well into the wood, color and UV protect. Includes UV rays to prevent graying, fading, flaking, staining and chalking. These products are not recommended for particle board or composite decking materials.

BEST LOOK EXTERIOR OIL-BASED DECK AND SIDING TONERS

Provides a rich, penetrating finish that highlights and beautifies wood's natural appearance. This product penetrates naturally and includes moisture-repelling and minimal UV protection. Recommended for use on weathered wood. *(Color sample for illustration only)*

COVERAGE:
Semi-Transparent Stains & Toners - One gallon will cover approximately 250 sq. ft. on smooth wood and 100 to 200 sq. ft. on rough, porous wood. One coat is recommended. Stain color may vary due to application and color of wood. You may wish to use a primer on weathered wood to achieve the desired color.

SPREAD RATE:
Semi-Transparent Stains & Toners - 1.5 to 2.0 gallons will cover 200 to 400 sq. ft. depending on the wood. Oil-based toners of the wood. Not recommended for maximum durability on surfaces subjected to foot traffic.

SURFACE PREPARATION:
Proper surface preparation is necessary to promote optimal stain penetration and adhesion. Surfaces to be stained must be clean and absorbent. Use an appropriate cleaner to remove contaminants such as dirt, dust, dirt, and grease. Remove all works with a quality Stain Remover. Remove all previous wood stains. Apply the stain to the wood surface. Apply the stain to the wood surface. Apply the stain to the wood surface. Apply the stain to the wood surface.

APPLICATION:
These products may be applied to damp surfaces. The product may be cleaned and stained in one day. When using a spray gun, apply the stain to the wood surface. Do not allow the stain to dry completely before applying. Apply the stain to the wood surface. Apply the stain to the wood surface. Apply the stain to the wood surface.

DRY TIME:
SOLID - Recoat within 2 hours. Dry to touch: 1 hour. 50°F allow 24-48 hours for recoat.
SEMI-TRANSPARENT - Recoat within 24 hours. Dry to touch: 12 hours. Use after 24 hours.

CLEAN UP:
LATEX & MODIFIED ALKID/ACRYLIC - Clean all tools, spills and splatters immediately with soap and water.

Oil - Clean all tools, spills and splatters immediately with mineral spirits. Follow manufacturer's instructions for use of mineral spirits.

MAINTENANCE:
Allow 30 days before washing.

Manufactured by The Sherwin-Williams Company
Distributed exclusively by De S. Best Corp., Fort Worth, Texas 76101
409-229-9911