



Best
Quality Paints

BEST LOOK

PORCH & FLOOR ENAMELS



Best Look® Porch and Floor Enamels offer maximum protection against dirt and water on your beautiful interior or exterior surfaces. Best Look® Porch and Floor Enamels are formulated to demonstrate exceptional durability and color retention on high traffic areas of your home or business. Let Best Look® Porch and Floor Enamels beautify your new surfaces and restore the look of old surfaces.



INTERIOR/EXTERIOR FLOOR ENAMELS




PREMIUM ALKYD POLYURETHANE PORCH AND FLOOR ENAMEL

Interior/Exterior
• Exceptional durability and color retention in heavy traffic areas
• Exceptional leveling properties
• Resistant to moisture, household chemicals and soaps
• Residential and commercial applications
• Available in Gloss finish
• Recommended for wood, metal and concrete floors, steps, porches, patios, railings, walkways and trim
• Excellent for use on factory or warehouse floors, and boat decks
• Package colors available and blendable to all 16 Best® colors

HEAVY DUTY 100% ALKYLIC PORCH AND FLOOR ENAMEL

Interior/Exterior
• Self-Priming
• Exceptional leveling properties
• Resistant to moisture, household chemicals and soaps
• Residential and commercial applications
• Available in Satin and Gloss finishes
• Ideal for wood, metal and concrete floors, walkways, porches, patios, railings, walkways and trim
• Available in Light Gray and Dark Gray package colors and blendable to all 16 Best® colors



**PREMIUM 100% ACRYLIC
LATEX GARAGE FLOOR
ENAMEL**


Interior/Exterior
• 100% Acrylic Latex formula
• Residential and commercial applications
• Resistant to moisture, concrete moisture
• Mar and abrasion resistant
• Resistant to hot tire pick-up
• Exceptional leveling properties
• Ideal for garage floors, patios, porches and driveways
• Available in Satin finish
• Available in Light Gray and Dark Gray package colors only

Questions about painting? Call toll free 1-800-284-4181
800-600-0011

Best
Quality Paints

BEST LOOK

PORCH & FLOOR ENAMELS



BEST LOOK-ACRYLIC LATEX PORCH AND FLOOR ENAMEL is an interior/exterior gloss enamel that beautifies new surfaces and restores the look of worn surfaces. It offers exceptional leveling properties, durability and color retention in high-traffic areas. This paint is ideal for floors, patios, porches, steps and trim. Adhere to properly prepared concrete, wood and metal.

BEST LOOK-ACRYLIC LATEX PORCH AND FLOOR ENAMEL is an interior/exterior enamel that is available in satin and gloss finishes. Formulated with 100% Acrylic Latex to ensure adhesion to properly prepared concrete, wood and metal. This paint has self-leveling properties for a smooth finish and water resistant finish. It is ideal for floors, patios, porches, steps and trim.

BEST LOOK-ACRYLIC LATEX SATIN GARAGE FLOOR ENAMEL is a 100% Acrylic Latex that offers exceptional leveling properties. It is formulated to seal and protect concrete surfaces and provides a durable satin finish that resists hot tire pick-up and abrasion. Ideal for garage floors, carpets and patios.

COLOR GALLERY

BEST LOOK® PORCH & FLOOR ENAMELS

BEST LOOK® ALKYD POLYURETHANE GLOSS PORCH AND FLOOR ENAMEL

SURFACE PREPARATION:
STEP 1 - Clean the surface. The entire surface should be scrubbed with a detergent and water. Thoroughly dry areas should be spot cleaned. If oil or grease is present, a specialty cleaner may be needed. If dryness is present, a solution of one part bleach and four parts water will clean the surface.

STEP 2 - Prime surface thoroughly after cleaning. The entire area must be free of oil, grease, dirt, detergent or other contaminants in order for the paint to properly adhere to the surface.

STEP 3 - Remove dust or existing paint on previously painted floors, remove all pooled or dripped paint prior to painting. All dried painted surfaces by sanding and remove sanding dust for better adhesion.

STEP 4 - Etch bare concrete. New concrete must be cured for at least 30 days. Follow Step 1 & 2. Wet surface with clean water. Apply a solution of 2 parts water and 1 part muriatic acid, at a rate of 25 sq. ft. per gallon. Scrub surface with a stiff brush for approximately 30 minutes until bubbling stops. Rinse surface free three times and allow to dry. Surface should have a texture similar to 120-grit sandpaper.

STEP 5 - Repair damaged surface. Use appropriate patching compound to repair cracked or deteriorated areas. Allow surface to dry.

STEP 6 - To ensure the surface is sufficiently dry, tape a 2" x 2" sheet of plastic on the base surrounding all edges. Allow 48 hours, if moisture, deterioration or condensation is found under the plastic, locate the source of moisture and correct before painting.

STEP 7 - Apply paint. Stir paint well. Do not thin. If using more than one gallon of the same product, mix them together as one container to ensure color uniformity. For best results, use premium quality applicators. Apply at temperatures above 50°F and at a rate of 40 sq. ft. per gallon. Allow 24 hours dry time before applying a second coat.


Manufactured by The Sherwin-Williams Company
Distributed exclusively by The Best Corp. For More Info, Contact 800-600-0011




Best
Quality Paints

INDUSTRIAL

INTERIOR / EXTERIOR



Trust Do it Best® Industrial Enamels to meet your performance demands for all your light to moderate industrial applications. Our Alkyd and Waterborne Industrial Enamels and Primers are formulated to provide excellent durability, adhesion and protection in most commercial or industrial environments. Do it Best® Industrial Enamels are suitable to a wide variety of colors, including form and implement colors. Also available in packaged DSH-A and ANSI colors.



Best
Quality Paints

INTERIOR/EXTERIOR

Waterborne Industrial Enamel

Features & Benefits:

- Fast drying
- Corrosion resistant
- Durable & early recoat
- Single component
- **Substrates**
 - Direct to metal
 - Primed with galvanized metal
 - Prepared steel, concrete, masonry, drywall
 - **Uses**
 - Maintenance, buildings, machinery, farm implements, equipment, new construction, filling storage tank exteriors, structural steel
 - USDA approved for incidental food contact

Sheen: Flat, Satin
Colors: White, Black, Navy Blue, Neutral Base, DSH-A Yellow, Black, Safety Orange, DSH-A Red

Waterborne Industrial Primer/Finish

Features & Benefits:

- May be used as a primer or undercoat
- Fast water based formula or also a primer/topcoat system
- Fast drying
- Corrosion, chemical & early recoat resistant
- Early moisture resistance
- Single component
- **Substrates**
 - Iron, steel, aluminum, galvanized metal, masonry, concrete, PVC & fiber glass
 - **Uses**
 - Maintenance primer, bar ends, new construction, buildings, machinery, farm implements, equipment, filling storage tanks, fill coats
 - USDA approved for incidental food contact

Sheen: Flat
Package Colors
White

Alkyd Industrial Enamel™

Features & Benefits:

- Chip & fade resistant
- Corrosion, chemical & impact resistant
- Plastic adhesion
- Low temperature application
- **Substrates**
 - Direct to metal
 - Primed with galvanized metal, aluminum & galvanized metal
 - Prepared steel, masonry & block
 - **Uses**
 - Maintenance, machinery, farm implements, automotive, handrails, rolling stairs, bridges
 - USDA approved for incidental food contact

Sheen: Flat, Satin
Colors: White, Black, Navy Blue, Neutral Base, DSH-A Yellow, Black, Safety Orange, DSH-A Red, Aluminum

Alkyd Industrial Primer™

Features & Benefits:

- Corrosion & heat resistant
- Compatible with alkyd enamels
- **Substrates**
 - Iron, steel & previously painted surfaces
 - **Uses**
 - Maintenance primer, structural steel, equipment, machinery, farm implements, handrails, doors
 - USDA approved for incidental food contact

Sheen: Flat
Package Colors
White, Black, Navy Blue

*Refer to Product Data Sheets for recommended product uses, application procedures and other important information.
†Always wear protective gear when using industrial products.
‡Always wear products may not be available in all regions.

Manufactured by The Sherwin-Williams Company
Distributed exclusively by The Best Corp. For More Info, Contact 800-600-0011